

POLITERM® BLOWREADYMIX

((

FAN FOR POLITERM® BLU READY MIX LOADING IN CEMENT MIXER

POLITERM® BLOW READY MIX Fan for politerm® blu ready mix loading in cement mixer


Fan for the loading of Politerm® Blu Ready Mix into cement mixer.

Iron framework with:

- · Engine's control panel.
- TYPE OF EQUIPMENT


 Transfer fan of the beads.
 - · Metal pipe for the beads loading with flexible top part.
 - · Wheels for the handling.
 - · Adjusting device for the loading pipe positioning.
 - · 20 m of power supply cable + industrial three-phase 16A plug.
 - · Phase inverter.

Power supply:	400 V
Voltage:	380 V
Power:	0, 75 Kw
Weight:	300 kg
Hopper capacity:	760 L



TECHNICAL SCHEMA

TECHNICAL CHARACTERISTICS



All the indications provided in this technical sheet are purely approximate and not binding for legal purpose. The data listed has been gathered from laboratory test and it hence follows that in practical applications on building sites the final products may be subject to variations depending on meteorological conditions and the installation. The user must always check suitability of the product for its specific use, undertaking all liability implicit in and deriving from use of the product, as well as comply with all methods and instruction for use generally referable to "workmanlike" execution. Edilteco S.p.A reserves the right to change the contents of this mechanical data sheet on its final judgment. The spreading of this data sheet through any media, supersedes and cancels the validity of any other technical data sheet previously published.











E&MP Engineering Machines Plants Division

DS POLITERM® BLOW READY MIX . Rev 08/2018 . GB

